

(19)

(11) Publication number: **061456**

Generated Document

PATENT ABSTRACTS OF JAPAN(21) Application number: **04299723**(51) Intl. Cl.: **C09J153/02 B21C 37/06 B29C 63/3**
15/08(22) Application date: **10.11.92**

(30) Priority:

(43) Date of application
publication: **27.05.94**(84) Designated contracting
states:(71) Applicant: **SEKISUI CHEM CO LTD**(72) Inventor: **IKETANI YASUO**

(74) Representative:

BEST AVAILABLE CC

**(54) ADHESIVE
COMPOSITION FOR
SYNTHETIC RESIN LINING
AND PRODUCTION OF
PIPE LINED WITH
SYNTHETIC RESIN**

(57) Abstract:

PURPOSE: To obtain the subject adhesive composition excellent in sustained adhesiveness and thermal shock resistance, comprising a specific adhesive and a saturated polyester resin, etc.

CONSTITUTION: This adhesive composition comprises (A) 100 pts.wt. of an adhesive of formula A-B-A or A-B (A is a block consisting virtually of a monovinyl- substituted aromatic polymer; B is a block consisting virtually of conjugated diene polymer or a hydrogenated product thereof) containing e.g. a styrene-butadiene-styrene block copolymer as the main component and (B) pref. 5-30 pts.wt. of a saturated polyester resin or polyolefinic copolymer. The outer peripheral surface of a synthetic resin pipe is coated with this adhesive composition followed by inserting this coated resin pipe into a metallic pipe and then either shrinking the diameter of the metallic pipe or expanding the diameter of this resin pipe to preferably obtain the other objective synthetic resin-lined pipe.

COPYRIGHT: (C)1994,JPO&Japio

BEST AVAILABLE COPY